



For Model Numbers:

1" Hitch Ball Hole	1 1/4" Hitch Ball Hole
DT-LBM4200	DT-LBM5200
DT-LBM4400	DT-LBM5400
DT-LBM4600	DT-LBM5600

BM Use & Care Instructions

Congratulations on your purchase of a new Fastway Flash Aluminum Ball Mount. Read these instructions thoroughly to become familiar with proper setup and maintenance procedures. This will ensure that your Flash Ball Mount will give you maximum performance, and years of service. Keep them in a safe place as a reference for future information.

Remember to register your product warranty.

IMPORTANT SAFETY INFORMATION

Failure to follow all safety warnings may result in severe injury or death.

⚠️ WARNING

- Read, understand, and follow all safety warnings, setup, use, and maintenance instructions of your trailer, tow vehicle, and hitching equipment before installing your Flash ball mount or towing your trailer.
- Never cut, weld, grind, bend, heat, or modify ball mount hitch components in any way.
- It is the driver's responsibility to properly install and adjust equipment and adjust driving habits to match towing conditions. The driver is responsible for their own safety and the safety of passengers.
- Never exceed the specified weight ratings for the trailer, tow vehicle, receiver hitch, ball mount, hitch ball, or any other towing equipment.
- Always use a hitch ball with the correct diameter shaft to fit the hole in the ball mount.

Hitch Ball
Not Included



MAX TONGUE WEIGHT:	1,000 LBS.
MAX TRAILER WEIGHT:	10,000 LBS.

- Always use a hitch ball with a rating that equals or exceeds the Gross Trailer Weight (GTW).
- Do not impact the ball mount on the ground in dips or swales while driving. Do not back into things with your ball mount or attached trailer (loading docks, large rocks, etc.). If your ball mount has been impacted in any way, thoroughly inspect it for damage before towing. If it is bent or damaged, replace it.
- Do not unlock the ball mount from the receiver while the ball mount is under load from an attached trailer.
- Always use a hitch ball size that correctly matches your trailer coupler size and make sure it is coupled securely before towing.
- Check all towing hardware before each trip.

Proudly Made in the USA

⚠ CAUTION

- Never use the ball mount as an anchor point for a chain or tow strap.
- Always load the trailer correctly. Follow the trailer and tow vehicle manufacturer's recommendations for placement and quantity of cargo.
- Do not tow your trailer through profound ditches, dips, or swales.
- Replace all worn, faded, or unreadable warning stickers on the ball mount immediately.

USING YOUR BALL MOUNT

Install the hitch ball. Flash ball mounts come with either a 1" or 1-1/4" hitch ball mounting hole. Install a hitch ball that has the correct diameter shank to fit the hole in your ball mount. Make sure to torque the hitch ball nut to

the torque specification from the hitch ball manufacturer. Before you tow, grease the hitch ball. This protects the ball and the inside of your trailer coupler.

Use 5/8" diameter hitch pin to secure the ball mount in the receiver of your tow vehicle. To help protect your ball mount from theft, we recommend using the Fastway locking hitch pin, part # DT-30005 for 2" receivers, or DT-31005 for 2-1/2" receivers.

CARE AND MAINTENANCE

DO NOT use degreasers or harsh cleaners. A simple solution of mild soap and water is best for aluminum. Aluminum rim cleaner and a good automotive wax will help maintain the polished luster of the aluminum.

Visit our YouTube channel for a detailed video of the Flash BM.



[YouTube.com/FastwayTrailer](https://www.youtube.com/FastwayTrailer)



[Facebook.com/FastwayTrailer](https://www.facebook.com/FastwayTrailer)



[Twitter.com/FastwayTrailer](https://twitter.com/FastwayTrailer)

DO NOT RETURN THIS PRODUCT TO THE RETAILER

For Warranty Claims or Customer Support Contact Fastway Trailer Products Directly

8:00 a.m. - 5:00 p.m. Mon. - Fri. MST at 877.523.9103 or via email at CustomerSupport@FastwayTrailer.com

Limited 1 Year Warranty: Fastway Trailer Products warrants the Fastway Flash Ball Mount against latent defects in materials and workmanship under normal use and service, chrome and corrosion and ordinary wear and tear is excepted, to the original owner for a period of 1 year from the first date of purchase at retail up to the value of its original purchase price. If this product is latently defective it will be replaced or repaired when a proper return authorization is obtained and the product is returned with transportation charges prepaid to Fastway Trailer Products. Fastway Trailer Products shall not be required to replace or repair any products damaged as a result of improper installation, alteration, unreasonable use, or improper maintenance including, without limitation, loading the product beyond the factory rated load capacity. This warranty does not include labor charges nor does it include transportation charges for returning the product to the consumer. To the extent allowed by law, Fastway Trailer Products shall not be liable for any incidental, consequential, or any other damages including, without limitation, breach of any implied warranty, merchantability, or fitness for a particular purpose of any Fastway product. In no event shall Fastway Trailer Products be liable for any damages other than the replacement or repair of the affected part. Authorization and warranty procedure may be obtained by calling Fastway Trailer Products customer support at 877.523.9103.

Fastway Trailer Products, 353 South 1100 West, Provo, UT 84601
(877) 523-9103 FastwayTrailer.com