

# FLASH™

## For Ball Mount Models:

42-00-2400 (4" drop / 5" rise)

42-00-2800 (8" drop / 9" rise)

42-00-2600 (6" drop / 7" rise)

42-00-2900 (10" drop / 11" rise)

Congratulations on your purchase of a new Fastway® Flash™ adjustable aluminum ball mount. Please read these instructions thoroughly to become familiar with proper setup and maintenance procedures. This will ensure that your Flash ball mount will give you maximum performance and years of service.

KEEP THESE INSTRUCTIONS in a safe place for future reference.

KEY NUMBER:

Write the key number to your locking pins here for easy replacement if they are lost.

## IMPORTANT SAFETY INFORMATION

Failure to follow all safety warnings may result in severe injury or death.

### ⚠ WARNING

- Read, understand, and follow all safety warnings, setup, use, and maintenance instructions of your trailer, tow vehicle, and hitching equipment before installing your Flash ball mount or towing your trailer.
- Never cut, weld, grind, bend, heat, or modify ball mount components in any way.
- It is the driver's responsibility to properly install and adjust the equipment and to adjust driving habits to match towing conditions. The driver is responsible for their own safety and the safety of passengers.
- Never exceed the specified weight ratings for the trailer, tow vehicle, receiver hitch, ball mount, hitch ball, or any other towing equipment.
- Always use a hitch ball size that correctly matches your trailer coupler size and make sure it is coupled securely before towing.
- Do not impact the ball mount on the ground. Do not back into things with your ball mount or an attached trailer (i.e. loading docks, trees, etc.). If your ball mount has been impacted in any way, thoroughly inspect it before towing, and if it is bent or damaged DO NOT tow; replace it.
- Do not try to adjust ball holder height while the ball mount is under load from an attached trailer.
- Check all towing hardware before each trip. Do not tow your trailer until all pins have been checked for wear, visually verifying that the height adjustment pin is properly inserted through the height adjustment hole, and that the hairpin clip is in place.
- Do not tow with ball mount if any part of it shows excessive wear.
- Always use an appropriately sized adapter sleeve when using a tow vehicle equipped with a 2½" or 3" receiver hitch.

### ⚠ CAUTION

- Always tow with the hitch ball adjusted to the correct height for the trailer being towed.
- Always load trailer correctly. Follow trailer and tow vehicle manufacturer's recommendations for placement and quantity of cargo.
- Do not tow your trailer on excessively rough roads.
- Do not tow your trailer through profound ditches, dips, or swales where the ball mount could impact the ground.
- Replace all worn, faded, or unreadable warning stickers on the ball mount immediately.

# E SERIES™

## Pin-style Adjustable Aluminum Ball Mount

### Use and Care Instructions

Date of Purchase:

BALL SIZE	MAX TRAILER WT. LBS.	MAX TONGUE WT. LBS.
2"	8,000	1,000
2 5/16"	10,000	




Figure 1



1. Drop bar (shown in down, or "drop" position)
2. Height adjustment holes
3. Height adjustment pin
4. Ball holder
5. Hairpin clip
6. Optional locking pin set (keyed alike hitch pin and ball height adjustment pin)

Please register your product warranty. See warranty information on back.

Proudly Made in the USA

## Installation/Use Instructions

The most important consideration when setting up your Flash ball mount is to make sure the trailer is as close to level (parallel to the ground) as possible while being towed. To do this, you must set the ball mount up to compensate for any drop or sag caused by the tongue weight of the trailer.

1. Level the trailer by parking it on a smooth flat surface. Measure from the ground to the frame at both the front and rear of the trailer. Use the tongue jack to make adjustments until it is level (both front and rear measurements are the same).
2. Back the tow vehicle up to the trailer, leaving a few feet of working space between them.
3. Slide the drop bar into the tow vehicle's receiver hitch and pin it into place.
4. Measure from the ground to the bottom of the coupler on the trailer, then pin the ball holder into place on the drop bar at that height, with the correctly sized hitch ball for your trailer coupler facing up. See **Figure 2**. You may need to invert the drop bar and use it in the rise position to reach the correct ball height for your particular trailer.




Figure 2

*Figure 2: Top of ball holder height should initially be set equal to the bottom of the coupler socket height with the trailer parallel to the ground, then **adjusted upward** to compensate for the distance it drops when the tongue weight is being carried.*

*Rise or drop is measured from the top of the receiver opening to the top of the ball holder.*



**Always secure the height adjustment pin with the hairpin clip before placing a load on the ball mount.**

5. Couple the trailer to the tow vehicle, and drop the full tongue weight of the trailer on the ball mount.
6. Re-measure the coupler height, and compare it to the first level measurement. The difference between these is the distance the ball mount should be adjusted upward to compensate for the trailer's tongue weight.
7. Uncouple the trailer.
8. Raise the ball holder to the adjusted towing height; and re-pin it into place.  
It is better to tow with the trailer level, or with the tongue angled slightly downward. If the adjusted towing height falls between two adjustment holes, choose the lower of the two.
9. Repeat this process if the loading of your trailer changes, or to set the ball mount up for a different trailer.

## Care and Maintenance

1. Storage - Regularly remove your Flash ball mount from the receiver tube and wipe away any moisture and road grime from the hitch pin and the inside of the hitch pin bore in the drop bar. Keep a thin film of grease on the hitch pin. Doing so will help prevent galvanic corrosion around the hitch pin, which can cause it to become stuck in the receiver tube.

If you live in an area where salt and sand are used during winter to treat roadways, remove your Flash ball mount and store it inside the tow vehicle, instead of in the receiver during winter months. These elements are extremely abrasive and can damage the hand-polished finish of your ball mount.

2. Cleaning - Wipe away dirt and grime with a soft cloth. When cleaning the drop bar and ball holder surfaces, DO NOT use degreasers or harsh cleaners - simple mild soap and water is best for aluminum.
3. Towing - Always lubricate the hitch ball with heavy, multi-purpose grease or wheel bearing grease.
4. Polish - Maintain the shine of the ball mount by using aluminum wheel cleaner and applying an automobile wax to protect the finish.

## DO NOT RETURN THIS PRODUCT TO THE RETAILER

For Warranty Claims or Customer Support – CONTACT FASTWAY TRAILER PRODUCTS DIRECTLY

8:00 – 5:00 Mon. – Fri. MST at (877) 523-9103 or CustomerSupport@FastwayTrailer.com

**Limited 1 Year Warranty:** Fastway Trailer Products warrants the FLASH E series ball mount, excluding chrome and corrosion, against latent defects in materials and workmanship under normal use and service, ordinary wear and tear is excepted, to the Original owner for a period of 1 year from the first date of purchase at retail up to the value of its original purchase price. If this product is latently defective it will be replaced or repaired when a proper return authorization is obtained and the product is returned with transportation charges prepaid to Fastway Trailer Products. Fastway Trailer Products shall not be required to replace or repair any product damaged as a result of improper installation, alteration, unreasonable use, or improper maintenance including, without limitation, loading the product beyond the factory rated load capacity. This warranty does not include labor charges nor does it include transportation charges for returning the product to the consumer. To the extent allowed by law, Fastway Trailer Products shall not be liable for any incidental, consequential, or any other damages including, without limitation, breach of any implied warranty, merchantability, or fitness for a particular purpose of any Fastway product. In no event shall Fastway Trailer Products be liable for any damages other than the replacement or repair of the affected part. Authorization and warranty procedure may be obtained by calling **Fastway customer support at (877) 523-9103.**

Great products to make towing Faster and Easier. Get more info at **FastwayTrailer.com**



Keep your Fastway E series ball mount safe and secure with the optional keyed alike dual lock pack. Includes a 5/8" dia. long-span hitch pin that fits both 2" and 2 1/2" receivers, a 1/2" dia. ball height adjustment pin, and two keys. Hardened steel and chrome finished to match the shine on your ball mount! Part # 86-00-3660



The Fastway® Zip™ breakaway cable's coiled design keeps your cable from dragging.



Fastest and easiest automatic trailer tongue jack foot.



Fastest and easiest tandem axle wheel chock ever.

Fastway Trailer Products • 353 South 1100 West Provo UT 84601 • [FastwayTrailer.com](http://FastwayTrailer.com)

FLIN0117

Part # DTBM521